

F250 BODYFIBER



GENERAL TECHNICAL DESCRIPTION

Polyester-based, two-component fiberglass-reinforced filler.

Ideal for bridging and filling of large cavities.

Spreads effortlessly.

Easy sanding.

Quick drying properties.

SURFACE

Metallic
Polyester
Wooden

PRETREATMENT/CLEANING OF SUBSTRATE

The surface to be coated must be dry, clean, and free of grease and other contaminants. Ensure all substrates are thoroughly cleaned and dried at every step of the preparation process.



Sand substrate with an appropriate grit paper.



Clean the surface with 770 NORMAL / 771 FAST ANTISIL Degreaser.

Use 2 clothes wipe on, wipe off. Always wipe cleaner off the surface as long is wet, with a clean, dry cloth. Remove dust by air blowing and a tack cloth.

PRODUCT APPLICATION: Apply with a spatula when mixed with hardener directly on surfaces to treat.



Mix 100 parts FILLER with
2 - 3 parts BPO PASTE
HARDENER



Apply with the spatula
before it starts hardening
Pot life: 4 - 5 min /
23°C (73°F)



Non force dry
20 - 30 min /
23°C (73°F)



Short wave 5 – 8 min
Lamp distance: 60 - 70 cm



P 80 - P 120



Overcoat with HB BODY
1K & 2K Primers

SPECIFIC GRAVITY

1.6 ± 0.1 g/cm³

SOLID CONTENT

83 ± 2% Weight

VOC (2004/42/EC)

This is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 250 g/L. The VOC content in the ready for use form of this product is 250 g/L.
2004/42/II(b)(250)250

CLEANING OF EQUIPMENT

Clean after final use with
767 NITRO THINNER

REMARKS

- Application only with BPO Paste Hardener. Mix well with putty. Do not add more than 3% as this may cause staining of the topcoat finish.
- Do not apply to Etch Primer, Wash Primer, 1K Filler, TPA substrates and soft old paintwork.
- Do not apply at temperatures below 5°C (41°F).
- Dry sanding is always recommended.

STORAGE SHELF LIFE

Polyester materials have a limited shelf life. Guaranteed shelf-life 18 months in unused original containers stored in a cool place (5 - 25°C) (41 - 77°F).



Store in a cool place



Always wear protective equipment



Follow the application instructions mentioned in this TDS

BPO Paste Hardener contains organic peroxide and is an oxidant. If hardener comes in contact with the skin, wipe off immediately and wash with soap and water. After eye contact irrigate copiously with water and seek medical advice immediately.

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

NOVEMBER 2024